

# **The Mariano™**

**FP7930PWW Fan**



## **SPECIFICATION SHEET**



*Product Specifications Subject To Change*

# The Mariano™ Fan Assembly – FP7930PWW



Fan Assembly - FP7930PWW	
Distance from Ceiling to Blade Edge (with 4.5" DR)	9.31"
Blade Sweep / Pitch	52" / 13°
Housing Diameter	9.30"
Canopy Diameter	6.49"
Net Hanging Weight: (with Light Kit)	23.9 lbs

Distance from Ceiling to Bottom of Downlight	
Fan w/4.5" downrod	19"
Fan w/12" downrod	26.5"
Fan w/18" downrod	32.5"
Fan w/24" downrod	38.5"
Fan w/36" downrod	50.5"
Fan w/48" downrod	62.5"
Fan w/60" downrod	74.5"
Fan w/72" downrod	86.5"

Airflow / Energy Efficiency Info (120V)					
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts
High	165	6144	108	0.48	57
Med	109	3593	152	0.39	24
Low	53	1878	206	0.27	9

Available Finishes	
PWW	Pewter (DAMP)

## INSTALLATION REQUIREMENTS:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding a load of at least 50 lbs.

## ELECTRICAL REQUIREMENTS:

Ceiling fan requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

## MOTOR SPECS:

172 x 20 motor is designed for optimal performance with this fan.

## CONTROL OPTIONS:

The hand-held remote control (C24) with canopy receiver (RECFP5220) is included. Push button remote control will consist of 3 separate fan speeds, infinite light levels, and off position. Reversing switch located on fan housing. Optional wall control (C25) is available (to be used in conjunction with fan receiver).

## LIGHTING OPTIONS:

The 2-bulb (13 watt max CFL bulbs - included) downlight fixture with white swirl glass is included with this fan assembly. Maximum downlight wattage not to exceed 26 watts.

## DOWNROD OPTIONS:

The Mariano™ fan comes with a 1" Dia. x 4.5" downrod. Optional downrods are available in 12", 18", 24", 36", 48", 60", and 72". For installations requiring a longer downrod, a downrod coupler is available. The Mariano™ fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 4.5" downrod. Optional sloped ceiling ball kits (SCB1-52) are available for up to 52°. Call your local dealer for more information.

## BLADE SETS:

All-weather composite cherry finish curved blades.

## DAMP LOCATION:

Rated for damp location usage.



Copyright 2010 Fanimation, Inc.

10983 Bennett Parkway  
 Zionsville, IN 46077  
 Toll Free (888) 567-2055  
 FAX (866) 482-5215  
 Outside U.S. call (317) 733-4113  
 Visit Our Website [www.fanimation.com](http://www.fanimation.com)



2010/01