

# **The Multimax™**

**FP8008CH Series**



## **SPECIFICATION SHEET**



*Product Specifications Subject To Change*

# The Multimax™ Fan Assembly – FP8008CH



Fan Assembly - FP8008CH	
Distance from Ceiling to Blade Edge (with 6" DR)	10.7"
Blade Sweep / Pitch	52" / 14°
Housing Diameter	7.85"
Canopy Diameter	7.85"
Net Hanging Weight: (with Light Kit)	20.5 lbs

Distance from Ceiling to Bottom of Downlight	
Fan w/6" downrod	17"
Fan w/12" downrod	23"
Fan w/18" downrod	29"
Fan w/24" downrod	35"
Fan w/36" downrod	47"
Fan w/48" downrod	59"
Fan w/60" downrod	71"
Fan w/72" downrod	83"

Airflow / Energy Efficiency Info (120V)					
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts
High	156	5062	100	0.45	51
Med	118	3393	111	0.42	31
Low	81	2185	126	0.34	17

Available Finishes	
CH	Chrome with optional opal frosted glass light kit included

## INSTALLATION REQUIREMENTS:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding a load of at least 50 lbs.

## ELECTRICAL REQUIREMENTS:

Ceiling fan requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

## MOTOR SPECS:

172 x 18 motor is designed for optimal performance with this fan.

## CONTROL OPTIONS:

The hand-held touch screen remote control (CRL8TS) with receiver is included. Touch-screen remote has 3 separate fan speeds and off position, 1 to 12-hour fan timer and 3 min delay light-off feature. Reversing switch located on fan housing. Optional wall control (CWRL4WH/LA) is available.

## LIGHTING OPTIONS:

2-bulb (18-watt max low-profile CFL bulbs - included) downlight fixture is included with this fan assembly but not required for fan operation (cap is included for use in its place). Maximum downlight wattage not to exceed 36 watts.

## DOWNROD OPTIONS:

The Multimax™ fan comes with a 1/2" Dia. x 6" long downrod. Optional downrods are available in 12", 18", 24", 36", 48", 60", and 72". For installations requiring a longer downrod, a downrod coupler is available. The Multimax™ fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 4.5" downrod. Call your local dealer for more information.

## BLADE SETS:

A set of 4 reversible, cherry/mahogany, wood blades are included. Fan can be configured for 2-, 3- or 4-blade operation. Not recommended for Damp Location.

## DAMP LOCATION:

Fan not rated for Damp Location usage.



**10983 Bennett Parkway  
Zionsville, IN 46077  
Toll Free (888) 567-2055  
FAX (866) 482-5215**

**Outside U.S. call (317) 733-4113**

**Visit Our Website [www.fanimation.com](http://www.fanimation.com)**

