

PRODUCT DESCRIPTION

Patent Number: US D724,260S



Fixture Certified to NSF 2 standards
when assembled by KLUŠ

- Ability to create a line of light
- Easy assembly and disassembly
- Can be combined in straight and broken linear runs
- Simple design
- Designed to reach an IP65 waterproof rating

FINISH :

Silver anodized



Fill empty fields

Product nr.	
Fixture type	
Company	
Job name	
Date	

TECHNICAL SPECIFICATION

Application

- main lighting installation in existing drywall structures

Mounting

- mounted with clips in the mounting extrusion

Additional information

- minimal flange effectively masks the mounting gap
- space for LED strip: 0.95" / 24.2 mm

Extrusion bending

Minimum internal radius	Minimum external radius
3000 mm / 118.1"	3000 mm / 118.1"

- minimum radius - bending radius which when exceeded causes destruction (deformation, bending or lack of compatibility with other accessories, e.g. covers, end caps, etc.) of the extrusion,
- internal radius - refers to the extrusion bent so that the cover is facing the inside of the arch,
- external radius - refers to the extrusion bent so that the cover is facing the outside of the arch,
- irregular curves are possible after consultation and individual quotation,
- when bending anodized extrusions, one should be aware of cracking of the anode coating (which may be more or less visible depending on the radius).

Possibility of making a linear fixture with IP65 protection, which means the fixture is dustproof and waterproof in contact with water jets.


Achieving IP65 is possible with the following covers: LIGER-22, MUN-22 and HS-22.

Turn off LED lights during peak day light hours in outdoor applications to avoid excessive heat buildup which will result in diminished LED life.


AVAILABLE LENGTHS

Ref. nr.	surface finish	available lengths
B5553ANODA_1	Silver anodized	39.4"
B5553ANODA_2	Silver anodized	78.75"

TECHNICAL DRAWING



RELATED EXTRUSIONS



TEKNIK-ZM
Mounting track
Ref: C0399NA




TEKUS Mounting
track
Ref: B6638V1NA


RELATED PRODUCTS

COVERS

BLACK




LIGER-22 Cover
black
Ref: 17044



CLEAR COVERS



HS-22 Cover
clear
Ref: 17022



FROSTED COVERS



LIGER-22 Cover
frosted
Ref: 17032



G-K Cover
frosted
Ref: 17007





G-L Cover
frosted
Ref: 00413



HS-22 Cover
frosted
Ref: 17011



LIGER-22 Cover
frosted
Ref: 17032V1_10



SEMI-TRANSPARENT COVERS



G-K Cover semi-transparent
Ref: 00415



G-L Cover semi-transparent
Ref: 17008

END CAPS

REGULAR END CAPS




LOKOM-MET metalized End cap
Ref: 24103



LOKOM grey End cap
Ref: 24005

ACCESSORIES

FASTENERS & MOUNTING ACCESSORIES



KMA Spring
Ref: 00838



TEKNIK Clip
Ref: 24003

COMPONENTS FOR CONNECTING FIXTURES



ZM-NA-PION-45 Connector
Ref: 42315




ZM-NA-120 Connector
Ref: 42729




ZM-NA-PION-60 Connector
Ref: 42317



ZM-NA-PION-120 Connector
Ref: 42321




ZM-NA-45 Connector
Ref: 42339




ZM-NA-135 Connector
Ref: 42725



ZM-NA-90 Connector
Ref: 42723



ZM-NA-PION-90 Connector
Ref: 42726



ZM-NA-180 Connector
Ref: 42724



L135 Coupler
Ref: _



T90 Coupler
Ref: _




L90PW Coupler
Ref: _



L90PZ Coupler
Ref: _



L90 Coupler
Ref: _



L135PZ Coupler
Ref: _



L135PW Coupler
Ref: _



T135L Coupler
Ref: _




T135R Coupler
Ref: _



X135 Coupler
Ref: _

ADDITIONAL ITEMS



MP-22 Masking cover metallized
Ref: 17167




MP-22 Masking cover black
Ref: 17167L9005




MP-22 Masking cover white
Ref: 17167L9010

LED TAPES


HIGH EFFICACY




K-HE-1920-HD-24V
Ref: K-HE-1920-HD-24V



K-HE-0960-HD-24V
Ref: K-HE-0960-HD-24V




K-HE-1440-HD-24V
Ref: K-HE-1440-HD-24V




K-HE-0480-HD-24V
Ref: K-HE-0480-HD-24V


CRI95+




K-CR-1210-24V
Ref: K-CR-1210-24V




K-CR-1220-24V
Ref: K-CR-1220-24V



K-CR-1275-24V
Ref: K-CR-1275-24V




K-CR-1820-HD-24V
Ref: K-CR-1820-HD-24V




K-CR-1910-HD-24V
Ref: K-CR-1910-HD-24V




WP-K-CR-1210-24V
Ref: WP-K-CR-1210-24V



WP-K-CR-1220-24V
Ref: WP-K-CR-1220-24V




WP-K-CR-1275-24V
Ref: WP-K-CR-1275-24V



WP-K-CR-1910-HD-24V
Ref: WP-K-CR-1910-HD-24V



WP-K-CR-1820-HD-24V
Ref: WP-K-CR-1820-HD-24V




K-CR-0530-HD-24V
Ref: K-CR-0530-HD-24V




WP-K-CR-0530-HD-24V
Ref: WP-K-CR-0530-HD-24V


WHITE




K-1220-24V
Ref: K-1220-24




K-1275-12V
Ref: K-1275-12




K-1210-12V
Ref: K-1210-12




K-1210-24V
Ref: K-1210-24



K-1220-12V
Ref: K-1220-12



K-1820-HD-24V
Ref: K-1820-HD-24




K-1910-HD-24V
Ref: K-1910-HD-24




K-1275-24V
Ref: K-1275-24



WP-K-1210-12V
Ref: WP-K-1210-12



K-0530-HD-24V
Ref: K-0530-HD-24




WP-K-1220-12V
Ref: WP-K-1220-12



WP-K-1220-24V
Ref: WP-K-1220-24



WP-K-1220-IP65-24V
Ref: WP-K-1220-IP65-24V



WP-K-1275-12V
Ref: WP-K-1275-12



WP-K-1275-24V
Ref: WP-K-1275-24



WP-K-1820-HD-24V
Ref: WP-K-1820-HD-24




WP-K-1210-24V
Ref: WP-K-1210-24



WP-K-1640-HD-IP65-24V
Ref: WP-K-1640-HD-IP65-24




WP-K-1910-HD-IP65-24V
Ref: WP-K-1910-HD-IP65-24




WP-K-0530-HD-24V
Ref: WP-K-0530-HD-24V


RGB/ RGBW




WP-K-1275-RGB-12V
Ref: WP-K-1275-RGB-12V




K-1920-RGB+W-24V
Ref: K-1920-RGB+W-24V




K-1275-RGB-12V
Ref: K-1275-RGB-12V




WP-K-1920-RGB+W-24V
Ref: WP-K-1920-RGB+W-24V



K-1530-RGB+W-24V
Ref: K-1530-RGB+W-24V




WP-K-1530-RGB+W-24V
Ref: WP-K-1530-RGB+W-24V




K-1920-120-RGB-24V
Ref: K-1920-120-RGB-24V



WP-K-1920-120-RGB-24V
Ref: WP-K-1920-120-RGB-24V




K-1200-120-RGB-24V
Ref: K-1200-120-RGB-24V




K-0700-120-RGB-24V
Ref: K-0700-120-RGB-24V

ADJUSTABLE WHITE/ DIM TO WARM



K-22/50-1728-24V
Ref: K-22/50-1728-24V




WP-K-22/50-1728-24V
Ref: WP-K-22/50-1728-24V




K-30/18-1770-24V
Ref: K-30/18-1770-24V



WP-K-30/18-1770-24V
Ref: WP-K-30/18-1770-24V




K-30/18-1770-010V-24V
Ref: K-30/18-1770-010V-24V




WP-K-30/18-1770-010V-24V
Ref: WP-K-30/18-1770-010V-24V

LONG RUN




K-LR-1000-24V
Ref: K-LR-1000-24


RGB, RGBW CONNECTORS




C4-RGB+W-0W
Ref: C4-
RGB+W-0W




C6-RGB-0W
Ref: C6-RGB-0W



C11-RGB-1.5W
Ref: C11-
RGB-1.5W




C5-RGB+W-1.5W
Ref: C5-
RGB+W-1.5W




C14-RGB+W-6W
Ref: C14-
RGB+W-6W

WHITE LED STRIP CONNECTORS



C-SC-IP20
Ref: C-SC-IP20




C-SS-IP20
Ref: C-SS-IP20




C-SC-IP65
Ref: C-SC-IP65




C-SS-IP65
Ref: C-SS-IP65



C1-0W
Ref: C1-0W




C2-1.5W
Ref: C2-1.5W




C3-6W
Ref: C3-6W


ADJUSTABLE WHITE CONNECTORS



C7-AW-0W
Ref: C7-AW-0W




C8-AW-1.5W
Ref: C8-AW-1.5W




C9-AW-6W
Ref: C9-AW-6W


HD CONNECTORS



HD-C5-0W
Ref: HD-C5-0W



HD-C4-6W
Ref: HD-C4-6W



HD-C6-1.5W
Ref: HD-C6-1.5W

MARKETING MATERIALS



Presentation set
2
Ref: 90052